

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (Currently Amended) Data processing apparatus configured to receive signals from an input sensor, said signals corresponding to positions of mechanical interactions with said sensor, said apparatus comprising:

processing means configured to process data derived from said signals from said input sensor including ~~positional~~ data of a first type corresponding to the position of a mechanical interaction with said input sensor and data of a second data type corresponding to the absence of a mechanical interaction with said input sensor, wherein said processing means is configured to generate data representing a first character in response to processing an item of data of said second type followed by ~~positional~~ data of said first type corresponding to ~~a first~~ the position of a first mechanical interaction with said input sensor, and to generate data representing a different second character in response to processing an item of data of said second type following ~~positional~~ data of said first type corresponding to the position of a second different ~~second position~~ mechanical interaction with said input sensor.

2. (Currently Amended) Data processing apparatus according to claim 1, wherein said input sensor comprises a first conducting layer and a second conducting layer, each of said conducting layers having a conductive track positioned along opposing edges, and said data processing apparatus is configured to apply a voltage

between said conductive tracks of said first layer and to measure the voltage appearing at a conductive track of said second layer to determine ~~said positional data~~ of said first type.

3. (Currently Amended) Data processing apparatus according to claim 1, wherein said processing means is configured to:

(a) perform a first measurement relating to the position of a mechanical interaction with said sensor to generate a first measurement value;

(b) perform a second measurement relating to the position of said mechanical interaction to generate a second value; and

(c) generate said ~~positional data~~ of said first type only when said first value is within a predetermined amount of said second value.

4. (Currently Amended) Data processing apparatus according to claim 1, wherein said sensor is an XY position sensor, and said ~~positional data~~ of said first type corresponds to the position within a continuous area defined by said sensor.

5. (Previously Amended) Data processing apparatus according to claim 1, wherein said processing means is configured to measure a parameter of said sensor relating to the pressure applied to said sensor.

6. (Currently Amended) Data processing apparatus according to claim 5, wherein said ~~positional~~ data of said first type is generated by said processing means only when said measured parameter exceeds a predetermined amount.

7. (Previously Amended) Data processing apparatus according to claim 1, wherein said data processing apparatus comprises a hand-held computer.

8. (Currently Amended) Data processing apparatus according to claim 1, wherein said processing means comprises two processing devices, such that:

DI
Cmt
one of said processing devices is configured to receive said signals from said input sensor and to generate said positional data and data of said second data type; and

the second of said processing devices is configured to process said ~~positional~~ data of said first type and said data of said second ~~data~~ type to generate data corresponding to displayable characters.

9. (Original) Data processing apparatus according to claim 8, wherein second processing device is located in a computer.

10. (Previously Amended) Data processing apparatus according to claim 8, wherein said first processing device forms part of a keyboard assembly.

11. (Currently Amended) Data processing apparatus according to claim 8, wherein said first processing device is configured to generate a stream of data comprising ~~positional~~ data of said first type, and to send positional data to said second processing device only when an item of ~~positional~~ data of said first type differs from the immediately preceding item of sent data by more than a predetermined amount.

12. (Previously Amended) Data processing apparatus according to claim 1, wherein said input sensor forms part of said data processing apparatus, and said input sensor comprises at least two layers of conductive fabric.

DI
cmt
13. (Currently Amended) A method of processing signals received from an input sensor, said signals corresponding to positions of mechanical interactions with said sensor, wherein said method comprises:

processing data derived from said signals, said data comprising ~~positional~~ data of a first type corresponding to the position of a mechanical interaction with said input sensor and data of a second ~~data~~ type corresponding to the absence of a mechanical interaction with said input sensor, such that data representing a first character is generated in response to processing an item of data of said second type followed by an item of ~~positional~~ data of said first type corresponding to ~~a first~~ the position of a first mechanical interaction with said input sensor, and data representing a different second character is generated in response to processing an item of data of said second type following an item of ~~positional~~ data of said first type corresponding to the position of a second different second position mechanical interaction with said input sensor.

14. (Currently Amended) A method of processing signals according to claim 13, wherein said input sensor comprises a first conducting layer and a second conducting layer, each of said conducting layers having a conductive track positioned along opposing edges, and said data processing apparatus is configured to apply a voltage between said conductive tracks of said first layer and to measure the voltage appearing at a conductive track of said second layer to determine said ~~positional~~ data of said first type.

DI
amt
15. (Currently Amended) A method of processing signals according to claim 13, wherein said method includes the steps of:

(a) performing a first measurement relating to the position of a mechanical interaction with said sensor to generate a first measurement value;

(b) performing a second measurement relating to the position of said mechanical interaction to generate a second value; and

(c) generating ~~said positional~~ data of said first type only when said first value is within a predetermined amount of said second value.

16. (Currently Amended) A method of processing signals received from an input sensor according to claim 13, wherein said sensor is an XY position sensor, and said ~~positional~~ data of said first type corresponds to the position within a continuous area defined by said sensor.

17. (previously amended) A method of processing signals received from an input sensor according to claim 13, wherein a parameter of said sensor relating to the pressure applied to said sensor is measured, and said ~~positional~~ data of said first type is generated by only when said parameter exceeds a predetermined ~~amount~~ threshold value.

DI
cnt
18. (Currently Amended) A method of processing signals received from an input sensor according to claim 13, wherein a stream of data comprising ~~positional~~ data of first said type is generated, and an item of ~~positional~~ data of said first type is processed to generate data representing a character only when said item of ~~positional~~ data of said first type differs from the immediately preceding item of data in said stream by more than a predetermined amount.

19. (Currently Amended) Data processing apparatus configured to receive signals from an input sensor, said signals corresponding to positions of mechanical interactions with said sensor, said apparatus comprising:

a processor configured to process data derived from said signals received from said input sensor, said data comprising ~~positional~~ data of a first type corresponding to a ~~central~~ the center of the position of a mechanical interaction with said input sensor and data of a second ~~data~~ type corresponding to the absence of a mechanical interaction with said input sensor,

wherein said processor is configured to generate character data representing a first character in response to processing an item of data of said second type followed by

~~positional data of said first type~~ corresponding to a ~~first central~~ the center of the position
of a first mechanical interaction, and to generate character data representing a different
second character in response to processing an item of data of said second type
following ~~positional data of a first type~~ corresponding to a the center of the position of a
second different second central position mechanical interaction.

DI
cancel

20. (Currently Amended) Data processing apparatus according to claim 19,
wherein said data processing apparatus comprises a second processor configured to
generate said ~~positional data~~ of said first type and said data of said second type in
response to said signals received from said input sensor.
